

BOXER 532DX

Model Specifications

Engine System	
Type	Kubota D1105TD
HP / KW	32.8 / 24.5
Fuel Tank	9 Gallons
Reservoir Capacity	24 Gallons
Hydraulic Pressure (at Attachment)	3000 psi System Relief
Hydraulic Flow	14.5 GPM
Hydraulic Flow Ground Drive	0 - 14.5 GPM
Engine Warranty	2 Years
Product Warranty*	1 Year
Operator Platform	Spring Loaded
Creep Control	Variable

Units	English	
Wheel Base	37 in	940 mm
Wheel/Track Option	9 in	229 mm
Track Widening Undercarriage	34.5 - 43.5 in	876 - 1105 mm
Ground Clearance	5 in	127 mm
Length (w/Bucket)	96 in	2438 mm
Length (w/out Bucket)	77 in	1956 mm
Width (Fully Retracted)	35 in	876 mm
Width (Fully Extended)	43.5 in	1105 mm
Overall Height	54 in	1372 mm
Overall Operating Height (Fully Raised)	98 in	2489 mm
Hinge Pin Height (Fully Raised)	76 in	1930 mm
Dump Height	60 in	1524 mm
Dump Angle	37 degrees	37 degrees
Reach	34 in	864 mm
Tip Capacity	2100 lbs	953 kg
Operating Capacity, 35% of tip load.	735 lbs	333 kg
Operating Capacity, 50% of tip load.	1050 lbs	476 kg
Weight (w/out Bucket)	2671 lbs	1212 kg
Ground Pressure	3.6 psi	.248 bar
Ground Speed (Max)	3 mph	4.8 kph

